Product Datasheet

Ground Fault Circuit Interrupter, GFCI



Type/Model	GFCI
Manufacturer	OEM, China
Product Description	Duplex Universal Grounding Socket
Product Type	Special Outlet
Nature of Material	Polycarbonate module,
Type of Installation	Flush in solid walls
Type of inlets (Outlets)	Universal grounding
Rated Voltage: 230VAC Rated Current:10A-16A / 10A-20A Rated Residual Operationg Current: I∆ n=6MA,10MA Frequency: 50Hz-60Hz Breaking Capacity: 2000A Rated Short circuit Capacity: 3KA Instantaneous tripping type :C type,B type	
Breaking Capacity: 2000A Rated Short circuit Capacity: 3KA	
Breaking Capacity: 2000A Rated Short circuit Capacity: 3KA	
Breaking Capacity: 2000A Rated Short circuit Capacity: 3KA Instantaneous tripping type :C ty Protection of part mounted	pe,B type
Breaking Capacity: 2000A Rated Short circuit Capacity: 3KA Instantaneous tripping type :C ty Protection of part mounted inside the hollow walls	pe,B type IP2X
Breaking Capacity: 2000A Rated Short circuit Capacity: 3KA Instantaneous tripping type :C ty Protection of part mounted inside the hollow walls Material	pe,B type IP2X Polycarbonate (PC)
Breaking Capacity: 2000A Rated Short circuit Capacity: 3KA Instantaneous tripping type :C ty Protection of part mounted inside the hollow walls Material	pe,B type IP2X Polycarbonate (PC)
Breaking Capacity: 2000A Rated Short circuit Capacity: 3KA Instantaneous tripping type :C ty Protection of part mounted inside the hollow walls Material Color	pe,B type IP2X Polycarbonate (PC) White